

# LOT 1, PRW

FORM NO. GWS-31 10/94	<b>WELL CONSTRUCTION AND TEST REPORT</b> STATE OF COLORADO, OFFICE OF THE STATE ENGINEER	For Office Use only
-----------------------------	---	---------------------

1.	WELL PERMIT NUMBER <u>233096</u>
2.	OWNER NAME(S) <u>Jeffrey S. Auxier</u> Mailing Address <u>P O Box 2891</u> City, St. Zip <u>Edwards, CO 81632</u> Phone ( ) _____

3.	WELL LOCATION AS DRILLED: <u>NE 1/4 SW 1/4, Sec. 13 Twp. 49 N Range 8 E</u> DISTANCES FROM SEC. LINES: <u>1900</u> ft. from <u>S</u> Sec. line. and <u>2250</u> ft. from <u>W</u> Sec. line OR <small>(north or south) (east or west)</small> SUBDIVISION: <u>King Gulch</u> LOT <u>2</u> BLOCK _____ FILING(UNIT) _____ STREET ADDRESS AT WELL LOCATION: _____
----	--

4.	GROUND SURFACE ELEVATION <u>7600</u> ft. DRILLING METHOD <u>Air Percussion</u> DATE COMPLETED <u>June 6, 2001</u> TOTAL DEPTH <u>320</u> ft. DEPTH COMPLETED <u>320</u> ft.
----	--

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 15%;">Depth</th> <th>Description of Material (Type, Size, Color, Water Location)</th> </tr> <tr> <td>0-34</td> <td>Brown Sandy Clay &amp; Boulders</td> </tr> <tr> <td>34-283</td> <td>Brown Clay</td> </tr> <tr> <td>283-290</td> <td>Gray Sand &amp; Gravel <span style="float: right;">283</span></td> </tr> <tr> <td>290-320</td> <td>Gray Clay</td> </tr> <tr> <td colspan="2">REMARKS: _____</td> </tr> </table>	Depth	Description of Material (Type, Size, Color, Water Location)	0-34	Brown Sandy Clay & Boulders	34-283	Brown Clay	283-290	Gray Sand & Gravel <span style="float: right;">283</span>	290-320	Gray Clay	REMARKS: _____		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3">6. HOLE DIAM. (in.)</th> </tr> <tr> <th>From (ft)</th> <th>To (ft)</th> <th></th> </tr> <tr> <td><u>8-3/4</u></td> <td><u>0</u></td> <td><u>40</u></td> </tr> <tr> <td><u>6</u></td> <td><u>40</u></td> <td><u>320</u></td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="5">7. PLAIN CASING</th> </tr> <tr> <th>OD (in)</th> <th>Kind</th> <th>Wall Size</th> <th>From(ft)</th> <th>To(ft)</th> </tr> <tr> <td><u>6-5/8</u></td> <td><u>Steel</u></td> <td><u>188</u></td> <td><u>+1</u></td> <td><u>39</u></td> </tr> <tr> <td><u>4</u></td> <td><u>Plastic</u></td> <td><u>250</u></td> <td><u>20</u></td> <td><u>260</u></td> </tr> <tr> <td colspan="5">PERF. CASING: Screen Slot Size: <u>1/8</u></td> </tr> <tr> <td><u>4</u></td> <td><u>Plastic</u></td> <td><u>250</u></td> <td><u>260</u></td> <td><u>320</u></td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">8. FILTER PACK:</th> <th colspan="2">9. PACKER PLACEMENT</th> </tr> <tr> <td>Material: _____</td> <td>Size _____</td> <td>Type _____</td> <td>Depth _____</td> </tr> <tr> <td>Interval _____</td> <td></td> <td></td> <td></td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="5">10. GROUTING RECORD:</th> </tr> <tr> <th>Material</th> <th>Amount</th> <th>Density</th> <th>Interval</th> <th>Placement</th> </tr> <tr> <td><u>Cement</u></td> <td><u>40gal</u></td> <td><u>8bags</u></td> <td><u>5-39</u></td> <td><u>poured &amp; vibrated</u></td> </tr> </table>	6. HOLE DIAM. (in.)			From (ft)	To (ft)		<u>8-3/4</u>	<u>0</u>	<u>40</u>	<u>6</u>	<u>40</u>	<u>320</u>	7. PLAIN CASING					OD (in)	Kind	Wall Size	From(ft)	To(ft)	<u>6-5/8</u>	<u>Steel</u>	<u>188</u>	<u>+1</u>	<u>39</u>	<u>4</u>	<u>Plastic</u>	<u>250</u>	<u>20</u>	<u>260</u>	PERF. CASING: Screen Slot Size: <u>1/8</u>					<u>4</u>	<u>Plastic</u>	<u>250</u>	<u>260</u>	<u>320</u>	8. FILTER PACK:		9. PACKER PLACEMENT		Material: _____	Size _____	Type _____	Depth _____	Interval _____				10. GROUTING RECORD:					Material	Amount	Density	Interval	Placement	<u>Cement</u>	<u>40gal</u>	<u>8bags</u>	<u>5-39</u>	<u>poured &amp; vibrated</u>
Depth	Description of Material (Type, Size, Color, Water Location)																																																																																	
0-34	Brown Sandy Clay & Boulders																																																																																	
34-283	Brown Clay																																																																																	
283-290	Gray Sand & Gravel <span style="float: right;">283</span>																																																																																	
290-320	Gray Clay																																																																																	
REMARKS: _____																																																																																		
6. HOLE DIAM. (in.)																																																																																		
From (ft)	To (ft)																																																																																	
<u>8-3/4</u>	<u>0</u>	<u>40</u>																																																																																
<u>6</u>	<u>40</u>	<u>320</u>																																																																																
7. PLAIN CASING																																																																																		
OD (in)	Kind	Wall Size	From(ft)	To(ft)																																																																														
<u>6-5/8</u>	<u>Steel</u>	<u>188</u>	<u>+1</u>	<u>39</u>																																																																														
<u>4</u>	<u>Plastic</u>	<u>250</u>	<u>20</u>	<u>260</u>																																																																														
PERF. CASING: Screen Slot Size: <u>1/8</u>																																																																																		
<u>4</u>	<u>Plastic</u>	<u>250</u>	<u>260</u>	<u>320</u>																																																																														
8. FILTER PACK:		9. PACKER PLACEMENT																																																																																
Material: _____	Size _____	Type _____	Depth _____																																																																															
Interval _____																																																																																		
10. GROUTING RECORD:																																																																																		
Material	Amount	Density	Interval	Placement																																																																														
<u>Cement</u>	<u>40gal</u>	<u>8bags</u>	<u>5-39</u>	<u>poured &amp; vibrated</u>																																																																														

11.	DISINFECTION: Type <u>HTH</u> Amt Used <u>3 oz.</u>
-----	---

12.	WELL TEST DATA: <input type="checkbox"/> Check box if Test Data is submitted on Form No. GWS 39 Supplemental Well Test TESTING METHOD <u>Air Lift</u> Static Level <u>221</u> ft. Date/Time measured <u>6-6-01 2:00pm</u> Production Rate <u>20</u> gpm Pumping level <u>320</u> ft. Date/Time measured <u>6-6-01 3:00pm</u> Test length (hrs.) <u>1</u> Remarks _____
-----	--

13. I have read the statements made herein and know the contents thereof, and that they are true to my knowledge. (Pursuant to Section 24-4-104, 105 & C.R.S., the making of false statements herein constitutes perjury in the second degree and is punishable as a class 1 misdemeanor.)

CONTRACTOR <u>American Drilling Service</u> Mailing Address <u>9934 Hwy. 50 Howard, CO 81233</u>	Phone <u>(719) 942-3568</u>	LIC No <u>1280</u>
Name/Title (Please type or print) <u>David Dewberry/President</u>	Signature 	Date <u>3-5-2</u>